



Stik-It Epoxy Putty

Material Safety Data Sheet

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Manufacturing Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents, and contractors of the information on the sheet.

SECTION I - GENERAL INFORMATION				
Black Swan Manufacturing Co. 4540 W. Thomas Street Chicago, IL 60651-3318 Telephone No: 1-773-227-3700 Fax No: 1-773-227-3705		For chemical emergencies during transportation only call INFOTRAC 1-800-535-5053 24 hours per day - 7 days a week		
Date Prepared 01/01/08		Trade Name STIK-IT EPOXY PUTTY		
SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION				
HAZARDOUS COMPONENTS	CAS#	APPROX%	ACGIH-TLV	OSHA-PEL
GLYCIDYL ETHERS OF BISPHENOL A RESINS	25068-38-6	13.05	N.E	N.E
TRI(DIMETHYLAMINOMETHYL)PHENOL	90-72-2	1.37	N.E	N.E
CRYSTALLINE SILICA	14808-60-7	12.64	N.E	N.E
*Title III Section 313 Supplier Notification: this product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency planning and community Right-to-Know Act of 1966 and of 40CFR372. This information must be included in all MSDS's that are copied and distributed for this material.				
<u>SHIPPING INFORMATION</u>		<u>SPECIAL HAZARD DESIGNATIONS</u>		
		<u>HMS</u>	<u>HAZARD RATING</u>	
HEALTH		1	0 - MINIMAL	
FLAMMABILITY		1	1- SLIGHT	

<p>NOT HAZARDOUS FOR SHIPPING PURPOSES.</p>	<p>REACTIVITY 0 2- MODERATE PROTECTIVE 3- SERIOUS EQUIPMENT A 4- SEVERE</p>		
<p>SECTION III - PHYSICAL DATA</p>			
<p>APPEARANCE PUTTY-LIKE</p>	<p>ODOR MILD AMINE ODOR</p>	<p>BOILING POINT N/A</p>	
<p>SPECIFIC GRAVITY (H2O=1) 1.5</p>	<p>VAPOR PRESSURE (mm Hg.) NIL</p>	<p>VOLATILE BY VOLUME (%) 0</p>	
<p>VAPOR DENSITY (AIR=1) N/A</p>	<p>EVAPORATION RATE (BUAC=1) NIL</p>	<p>SOLUBILITY IN WATER NONE</p>	
<p>SECTION IV - FIRE AND EXPLOSION HAZARD DATA</p>			
<p>FLASH POINT (METHOD USED)</p>	<p>FLAMMABLE LIMITS</p>	<p>LEL</p>	<p>UEL</p>
<p>NONE</p>	<p>(PERCENT BY VOLUME)</p>	<p>N/A</p>	<p>N/A</p>
<p>FIRE EXTINGUISHING MEDIA WATER SPRAY, FOAM, CO2, DRY CHEMICALS.</p>			
<p>SPECIAL FIRE FIGHTING PROCEDURES NONE</p>			
<p>UNUSUAL FIRE AND EXPLOSION HAZARD CO, ALDEHYDES, ACIDS, OXIDES OF SULFUR AND NITROGEN MAY BE FORMED.</p>			
<p>SECTION V - HEALTH HAZARD DATA</p>			
<p>PRIMARY ROUTES OR ENTRY _____ Inhalation <input checked="" type="checkbox"/> Skin contact <input checked="" type="checkbox"/> Eye contact <input checked="" type="checkbox"/> Ingestion</p>			
<p>EFFECT OF OVEREXPOSURE SKIN CONTACT: POSSIBLE IRRITANT AND SENSITIZER.</p>			

EYE CONTACT: POSSIBLE IRRITANT AND SENSITIZER.

INGESTION: IRRITATION OF INTESTINAL TRACT.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

NONE.

EMERGENCY AND FIRST AID PROCEDURES

INGESTION: INDUCE VOMITING.

SKIN CONTACT: WASH WITH SOAP AND WATER IMMEDIATELY.

EYE CONTACT: FLUSH WITH WATER CONSULT A PHYSICIAN.

SECTION VI - REACTIVITY

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	NONE

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE

HAZARDOUS DECOMPOSITION PRODUCTS

CO, ALDEHYDES, ACIDS, OXIDES OF SULFUR AND NITROGEN.

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	NONE

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

SPILLS OR LEAKS: DISPOSE OF IN NORMAL MANNER; NOT A HAZARDOUS WASTE.

NOT A POTENTIAL POLLUTANT.

WASTE DISPOSAL METHOD

INCINERATE IN FURNACE OR BURY IN LANDFILL ACCORDING TO APPLICABLE REGULATIONS.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

NONE REQUIRED.	
VENTILATION LOCAL EXHAUST - ONLY IF HEATED ABOVE 100Â° F.	
PROTECTIVE GLOVES POLYETHYLENE GLOVES FOR PROLONGED USE.	EYE PROTECTION SAFETY GLASSES
OTHER PROTECTIVE EQUIPMENT AND HYGIENIC PRACTICES N/A	
SECTION IX - SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING AVOID EYE CONTACT AND EXCESSIVE SKIN CONTACT.	
OTHER PRECAUTIONS WASH WITH SOAP AND WATER IMMEDIATELY AFTER USE. IF SANDING CURED PUTTY OR SUBSTRATES, WEAR EYE PROTECTION AND DUST MASK.	
This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.	

Black Swan Mfg. Co. Telephone:773-227-3700 E-mail: info@blackswanmfg.com
4540 W. Thomas Street Wats:800-252-5796 Web site:<http://www.blackswanmfg.com>
Chicago, IL 60651-3318 Fax:773-227-3705