

M A T E R I A L S A F E T Y D A T A S H E E T

FAMOWOOD WOOD FILLER - ALL COLORS

Page: 1

PRODUCT NAME: FAMOWOOD WOOD FILLER - ALL COLORS
PRODUCT CODE: 3710101000

HMIS CODES: H F R P
2*3 0 G

SECTION 1 - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ECLECTIC PRODUCTS, INC.
ADDRESS : 1075 ARROWSMITH
EUGENE OR 97402

EMERGENCY PHONE : (800) 535-5053
INFORMATION PHONE : (800) 767-4667
DATE REVISED : 6/20/00
DATE PRINTED : 10/18/05
NAME OF PREPARER : Regulatory Compliance

SECTION 2 - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE (mm Hg @ TEMP), WEIGHT PERCENT. Rows include Acetone, Methyl Ethyl Ketone, Wood Dust, Cellulose Nitrate, Solvent Naphtha, Zinc Stearate, Di-(Heptyl,nonyl,undecyl)phthalate, and Crystalline Silica.

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372. # Proposition 65 Statement: This product contains a chemical known to the State of California to cause cancer.

drying and cracking of the skin. EYES: Severe eye irritant. Direct contact may cause stinging, tearing, redness, swelling and possible eye damage.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No specific information available.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Swallowing can cause abdominal irritation, nausea, vomiting and diarrhea. Aspiration Hazard - Material can enter lungs and cause lung inflammation and/or injury.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, dizziness and nausea; in extreme cases, unconsciousness and death. Laboratory studies have shown that petroleum distillates may cause kidney, liver or lung damage. Reports have associated repeated or prolonged overexposure to solvents with permanent brain or nervous system damage. Laboratory animal studies of solvents contained in this product have shown some evidence of harm to the fetus. The relevance of these findings to humans is uncertain.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No

This product may contain a small percentage of wood dust particles. The International Agency for Research on Cancer (IARC) has classified wood flour as a nasal carcinogen. Sanding or machining cured wood fillers can produce wood dust irritating to the upper respiratory tract and lungs. Avoid breathing dust.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Persons with severe skin, liver, kidney or lung problems may aggravate these conditions with repeated exposure.

EMERGENCY AND FIRST AID PROCEDURES

EYES: Immediately flush with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention. SKIN: Wash skin with soap and water. If irritation occurs, get medical attention. INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Get medical attention. INGESTION: If swallowed, do not induce vomiting. Call a physician immediately.

=====**SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE**=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

DANGER. EXTREMELY FLAMMABLE. Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Place in non-leaking containers for proper disposal.

WASTE DISPOSAL METHOD

If this product in its purchased form becomes a waste material, it would be considered a hazardous waste. Dispose of in accordance with local, state, and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks, and flames. Vapors may accumulate and travel to ignition sources distant from handling site. Keep containers closed when not in use. Use with adequate ventilation. Work station conditions should be evaluated by management to determine proper personal protection and precautions.

OTHER PRECAUTIONS

Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld, or perform similar operations on or near containers. Static electricity may accumulate and create a fire hazard. Ground fixed equipment. Bond and ground transfer containers

and equipment.

===== SECTION 8 - CONTROL MEASURES =====

RESPIRATORY PROTECTION

If exposure may or does exceed occupational exposure limits, use a NIOSH approved respirator to prevent overexposure. In accordance with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors. Engineering or administrative controls should be implemented to reduce exposure. Dusts may be harmful if inhaled when cured putty is sanded. Wear dust mask.

VENTILATION

Use explosion-proof ventilation as required to control vapor concentrations below recommended levels.

PROTECTIVE GLOVES

Rubber or vinyl-coated gloves are recommended.

EYE PROTECTION

Safety glasses with side shields or goggles as appropriate.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

To prevent repeated or prolonged skin contact, wear impervious clothing. Eyewash fountains and safety showers should be easily accessible and ready for use.

WORK/HYGIENIC PRACTICES

Wash thoroughly after handling, and before eating, drinking, or smoking.

===== SECTION 9 - DISCLAIMER =====

To the best of our knowledge, the information provided herein is accurate, obtained from sources believed to be accurate. Since the conditions and methods of use of our product are beyond our control, we disclaim any and all liability arising out of the improper use of this product or the information provided herewith.