ULTRA PRO•MAXGLOSS WHITE PAINT

HMIS RATI	NG
Health	1
Flammability	4
Reactivity	3

KIMBALL-MIDWEST

MATERIAL SAFETY DATA SHEET

NFPA 704 RATING	
Health	1
Flammability	4
Reactivity	3
NFPA 30B LEVEL	
3	

P.O. BOX 2470 COLUMBUS, OH 43216-2470

CORPORATE & EMERGENCY TELEPHONE: 800-424-9300

1. PRODUCT IDENTIFICATION

PART NUMBER	80-880
PRODUCT NAME	ULTRA PRO• MAX GLOSS WHITE PAINT
	16OZ AEROSOL CAN
CHEMICAL FAMILY	N/A
DOT SHIPPING	Consumer Commodity ORM-D

2. HAZARDOUS INGREDIENTS

SPECIFIC CHEMICAL IDENTITY, COMMON NAMES	OSHA PEL	REL	ACGIH TLV	%
Acetone (00067-64-1)	1000ppm	250ppm	750ppm	17.8
Propane (00074-98-6)	1000ppm	1000ppm	2500ppm	15.7
Titanium Dioxide (13463-67-7)	-	-	-	11.9
N-Butane (00106-97-8)	-	800ppm	800ppm	9.3
Barium Sulfate (07727-43-7)	5mg/m ³	5mg/m ³	10mg/m ³	5.0
*Methyl Iso-butyl Ketone (00108-10-1)	100ppm	75ppm	75ppm	4.8
Gycol Ether EP (02807-30-9)	-	-	-	4.8
Isobutyl Acetate (110-19-0)	150ppm	150ppm	150ppm	4.8
Methyl Propyl Ketone (00107-87-9)	200ppm	150ppm	250ppm	3.4
*Xylene (01330-20-7)	100ppm	150ppm	150ppm	2.4

All chemical compounds marked with an asterisk (*) are toxic chemicals subject to the reporting of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture of trade name product is sold. This statement must not be detached. Any copy or redistribution of this Material Safety Data Sheet shall include this statement.

3. PHYSICAL DATA

BOILING POINT (RANGE)	
VAPOR PRESSURE PSIG @ 70°F	8300.00 hPa
VAPOR DENSITY (AIR = 1)	N/A
SOLUBILITY IN WATER	Slight
SPECIFIC GRAVITY (H2O = 1)	0.8725
MELTING/FREEZING POINT	N/A
EVAPORATION RATE (Ether=1)	>1
VOC content (by weight)	46%
APPEARANCE AND ODOR	White liquid/Aromatic

4. FIRE AND EXPLOSION DATA

FLASH POINT	19°C (-2°F)
UPPER EXPLOSIVE LIMIT (%)	. 13.0%
LOWER EXPLOSIVE LIMIT (%)	. 1.7%
EXTINGUISHING MEDIA	Extingusihing powder, CO ₂ , Sand. Do not use water!
	Containers can build up d to heat (fire). As in any fire, breathing apparatus pressure-

wear self-contained breathing apparatus pressuredemand (MSHA/NIOSH approved or equivalent) and full protective gear. FIRE AND EXPLOSION HAZARDSVapors may form explosive

mixture with air.

NFPA Flammability Hazard

5. HEALTH EFFECTS DATA
SHORT TERM EFFECTS OF EXPOSURE
ROUTE OF ENTRYSkin absorption, Inhalation, Ingestion, Eye contact, Skin contact
HEALTH HAZARDS
(ACUTE AND CHRONIC)
EYE CONTACT Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of a fine dust in the eyes.
INGESTION
INHALATION Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor. Prolonged inhalation may be harmful.
SKIN CONTACT Generally does not irritate the skin.

5. HEALTH EFFECTS DATA (CONT'D)

MEDICAL CONDITIONS GENERALLY
AGGRAVATED BY EXPOSURE Heart disease, respiratory
disorders.
FIRST AID PROCEDURES
EYE CONTACT Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.
SKIN CONTACT Wash with soap and water. Get medical attention if irritation develops or persists.
INGESTION If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
INHALATION Remove to fresh air; seek immediate medical attention; if breathing stops, begin artificial respiration; administer oxygen; obtain medical attention SPECIAL HEALTH EFFECTS
CARCINOGEN (OSHA Guidelines) None

6. REACTIVITY

STABILITY	Stable under normal conditions.
INCOMPATIBILITIES	No dangerous reations known
HAZARDOUS DECOMPOSITION	No decomposition if used according to specifications.
PRODUCTS	Fumes may contain CO ₂ , CO.
HAZARDOUS POLYMERIZATION	Will not occur under normal conditions
HAZARDOUS POLYMERIZATION CONDITION	IS None known

HAZARDOUS POLYMERIZATION CONDITIONSNone known
7. PRECAUTIONS FOR SAFE HANDLING & USE
PROTECTIVE EQUIPMENT REQUIREMENTS
WASH REQUIREMENTS Wash with soap and water.
SPILL OR LEAK PROCEDURES Absorb spill with inert material (e.g. dry sand or earth), then place in chemical waste container
WASTE DISPOSAL METHODS Dispose of in accordance with local, state and federal regulations
HANDLING & STORAGE Wash thoroughly after handling. Keep away from heat, sparks and flames. Store below 120°F.
OTHER PRECAUTIONS Use NIOSH approved respirator with an organic vapor cartridge; avoid prolonged breathing of

respirators is limited. 8. ADDITIONAL INFORMATION

vapors, protection provided by air purifying

Use self-contained breathing apparatus if TLV limits are exceeded. Do not eat or smoke while using. Wash hands after use. Use positive pressure air supplied respirator if there is potential for uncontrolled release, if exposure levels are unknown, or in any circumstance where air purifying respirators may not provide adequate protection.

THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT(S) ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. SUCH INFORMATION IS BASED UPON OUR RESEARCH AND ON DATA FROM OTHER RELIABLE SOURCES AND IS BELIEVED TO BE ACCURATE. NO GUARANTEE OF ACCURACY IS MADE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.

